

# TRELLEBORG

T - 9 0 0



TOTAL SOLUTIONS

  
**TRELLEBORG**  
WHEEL SYSTEMS



# PNEUMATIC TIRES



*The Trelleborg pneumatic tire range has been developed for heavy duty use on forklift trucks and other industrial vehicles. This line of tires offer customers an additional range of tires besides solid rubber and polyurethane products. All the tires have a lug type tread pattern which provides optimal grip and traction in every condition. The cross-ply or diagonal structure further insures high stability and maximum safety. The casing is of high tensile strength cord which offers good resistance to fatigue and improves comfort.*

- **NATURAL RUBBER**
- **GOOD RESISTANCE TO FATIGUE**
- **HIGH STABILITY MAXIMUM SAFETY**
- **OPTIMAL GRIP AND TRACTION**



## TRELLEBORG T-900

- **DESIGNED FOR HEAVY DUTY USE IN ALL APPLICATIONS**
- **PREMIUM TREAD COMPOUND FOR MAXIMUM TIRE LIFE AND WEAR RESISTANCE**
- **EXTRA WIDE TREAD FOR INCREASED STABILITY AND TRACTION**
- **REINFORCED SIDE WALL FOR IMPROVED PROTECTION AGAINST SIDE IMPACTS**
- **REINFORCED BEAD AREA THAT PROTECTS THE WHEEL FLANGES**
- **EXCELLENT RIDE QUALITY**



**T-900**

Size	P.R.	Recommended rim	Profile T-900	Inflated dimensions (mm)		Inflation pressure (±15%)		Weight Tire (kg)	Loadcapacity forklift up to 25 km/h (kg)	
				Width	O.D.	PSI	Bar		Front	Rear
5.00-8	10	3.00	*	140	468	145	10.00	6.9	1415	1090
18x7-8	16	4.33	*	168	462	145	10.00	10.0	2145	1650
6.00-9	12	4.00	*	160	543	145	10.00	10.9	1885	1450
6.50-10	12	5.00	*	182	590	130	9.00	14.0	2145	1650
23x9-10	20	6.50	*	230	585	145	10.00	25.5	3445	2650
7.00-12	14	5.00	*	191	680	130	9.00	18.9	2755	2120
7.00-12	16	5.00	*	191	680	145	10.00	19.0	2910	2240
23x10-12	16	8.00	*	245	600	116	8.00	25.2	3160	2430
23x10-12	20	8.00	*	250	600	145	10.00	26.7	3770	2900
27x10-12	16	8.00	*	250	685	116	8.00	28.7	3900	3000
7.00-15	14	5.50	*	200	756	127	8.75	24.3	3275	2520
7.50-15	16	6.00	*	215	785	145	10.00	31.3	3900	3000
28x9-15 (8.15-15)	14	7.00	*	230	710	145	10.00	26.2	3900	3000
8.25-15	14	6.50	*	247	841	116	8.00	36.9	4225	3250
250-15	20	7.50	*	240	742	145	10.00	36.1	5040	3875
300-15	20	8.00	*	290	840	130	9.00	47.9	6500	5000
7.50-16	12	6.00	*	215	805	116	8.00	30.1	3630	2790
9.00-20	14	7.00	*	265	1015	130	9.00	62.9	5850	4500
10.00-20	16	7.50	*	294	1080	130	9.00	75.2	6500	5000
11.00-20	18	8.00	*	305	1110	145	10.00	86.0	7800	6000
12.00-20	20	8.50	*	325	1145	145	10.00	101.3	8970	6900
12.00-20	24	8.50	*	325	1145	150	10.30	104.7	9710	7470
12.00-24	20	8.50	*	320	1245	145	10.00	120.5	9750	7500
14.00-24	24	10.00	*	380	1360	145	10.00	160.0	12350	9500

1) The above load capacities are based on available E.T.R.T.O and T.R.A. specifications for load and steering wheels on counterbalanced forklift trucks.

2) The Trelleborg pneumatic tires are available as complete sets (tire/tube/flap) or as tire & flap only.